



Product Data

A-Turf® EverGrass MT

Highlighted text indicates variable specifications. On turf construction, changing one of these impacts the others.

Pile Weight:	60 oz/sy recommended (55 oz to 66 oz typical)
Face Yarn Type:	100% polyethylene monofilament fiber (TenCate Monoslide Ultra XQ, four-ply) and 100% polypropylene texturized monofilament fiber, blended in dual yarn types and dual yarn thicknesses
Yarn Size:	Mono – 7,200 denier (4 ends/1,800 denier per end) Thatch – 4,600 denier (8 ends/575 denier per end)
Yarn Thickness:	310 microns
Pile Height (Finished):	1.75" recommended (1.75" to 2.25" typical)
Color:	Field Green, Field Green/Lime Green, Field Green/Olive Green
Construction:	Broadloom tufted
Stitch Rate:	9/3"
Tufting Gauge:	3/8"
Primary Backing:	TenCate XK TuffBack
Secondary Backing:	22 oz/sy urethane
Total Product Weight:	90 oz/sy (+/- 2 oz) (increase or decrease by adjusting pile weight)
Finished Roll Width:	15'
Finished Roll Length:	Up to 220'
Perforation (Outdoors):	3/16" holes on staggered 4" (approximate) centers
Turf Permeability:	> 20" +/- per hour
Infill Composition:	
Rubber & Sand (RS)	Ambiently ground SBR crumb rubber mixture and rounded or sub-angular, uniformly-sized silica sand
Sand-Only (S)	Uniformly sized silica sand <i>Note: All other proven synthetic and organic infill materials are available.</i>
Field Markings:	Tufted, inlaid and painted
Resilient ShockPad:	OPTIONAL with rubber & sand system, REQUIRED with sand-only system: 10mm (typical) porous composite (100% SBR particles bound with polyurethane) rubber pad (6010SH)

Call or email an A-Turf Representative for a precise spec, as specifications are subject to change without notice. A-Turf systems feature product components manufactured in the United States.