



Product Data

A-Turf® Mono

Highlighted text indicates variable specifications. On turf construction, changing one of these impacts the others.

Pile Weight:	45 oz/sy recommended (40 oz to 50 oz typical)
Face Yarn Type:	100% polyethylene monofilament fiber (TenCate Monoslide Ultra XQ – also available: Monoslide Classic or Monoslide Pro), six-ply
Yarn Size:	10,800 denier (6 ends/1,800 denier per end)
Yarn Thickness:	310 microns for Monoslide Ultra XQ, 260 microns for Monoslide Classic, 310 microns for Monoslide Pro
Pile Height (Finished):	2.25" recommended (2" to 2.5" typical)
Color:	Field Green, Field Green/Lime Green, Field Green/Olive Green (dual colors as alternating panels or blended fibers)
Construction:	Broadloom tufted
Stitch Rate:	9/3"
Tufting Gauge:	3/8"
Primary Backing:	TenCate XK TuffBack
Secondary Backing:	22 oz/sy urethane
Total Product Weight:	75 oz/sy (+/- 2 oz) (increase or decrease by adjusting pile weight)
Finished Roll Width:	15'
Finished Roll Length:	Up to 220'
Perforation (Outdoors):	3/16" holes on staggered 4" (approximate) centers
Turf Permeability:	> 20" +/- per hour
Infill Composition:	
Rubber & Sand (RS)	Ambiently ground SBR crumb rubber mixture and rounded or sub-angular, uniformly-sized silica sand
Rubber-Only (R)	Ambiently ground SBR crumb rubber (specify if preference is cryogenically processed) <i>Note: All other proven synthetic and organic infill materials are available</i>
Field Markings:	Tufted, inlaid and painted
Resilient ShockPad:	OPTIONAL: 10mm (typical) porous composite (100% SBR particles bound with polyurethane) rubber pad (6010SH)

Call or email an A-Turf Representative for a precise spec, as specifications are subject to change without notice. A-Turf systems feature product components manufactured in the United States.