



Product Data

A-Turf® Titan SS

Highlighted text indicates variable specifications. On turf construction, changing one of these impacts the others.

Pile Weight:	50 oz/sy with 1.5" pile height (typical) Must be installed over a ShockPad or approved pad or e-layer
Face Yarn Type:	100% polyethylene parallel-long slit fiber (TenCate XP Blade) and monofilament (TenCate Monoslide Ultra XQ, four-ply) blended in dual yarn types and dual yarn thicknesses
Yarn Size:	12,200 (4 ends/1,800 denier per end for Mono, 5,000 denier per end for XP)
Yarn Thickness:	100 microns for XP Blade, 310 microns for Monoslide Ultra XQ
Pile Height (Finished):	1.5" (typical)
Color:	Field Green, Field Green/Lime Green, Field Green/Olive Green (dual colors as alternating panels or blended fibers)
Construction:	Broadloom tufted
Stitch Rate:	13/3"
Tufting Gauge:	1/2"
Primary Backing:	TenCate XK TuffBack
Secondary Backing:	22 oz/sy urethane
Total Product Weight:	80 oz/sy (+/- 2 oz) with 1.5" pile height (typical)
Finished Roll Width:	15'
Finished Roll Length:	Up to 220'
Perforation (Outdoors):	3/16" holes on staggered 4" (approximate) centers
Turf Permeability:	> 20" +/- per hour
Infill Composition:	Sub-angular uniformly-sized sand, rounded uniformly-sized silica sand, sand with various coatings
Field Markings:	Tufted, inlaid and painted
Resilient ShockPad:	10mm (typical) porous composite (100% SBR particles bound with polyurethane) rubber pad (6010SH)

Call or email an A-Turf Representative for a precise spec, as specifications are subject to change without notice. A-Turf systems feature product components manufactured in the United States.