



Product Data

A-Turf® Premier XP

*Note: **Highlighted text** indicates variable specifications. On turf construction, changing one of these impacts the others. Call or email an A-Turf Representative if you want a precise specification.*

Pile Weight:	45 oz/sy recommended (40 oz to 50 oz typical)
Face Yarn Type:	100% polyethylene parallel-long slit fiber (Thiolon XP Tapeslide)
Yarn Size:	8,000 or 10,000 denier
Yarn Thickness:	100 microns
Pile Height (Finished):	2.25" recommended (2" to 2.5" typical)
Color:	Field Green
Construction:	Broadloom tufted
Stitch Rate:	9/3"
Tufting Gauge:	3/8"
Primary Backing:	TenCate XK TuffBack
Secondary Backing:	20 oz/sy urethane
Total Product Weight:	73 oz/sy (+/- 2 oz) (increase or decrease by adjusting pile weight)
Finished Roll Width:	15'
Finished Roll Length:	Up to 220'
Perforation (Outdoors):	3/16" holes on staggered 4" (approximate) centers
Turf Permeability:	> 20" +/- per hour
Infill Composition:	
Rubber & Sand (RS)	Ambiently ground SBR crumb rubber mixture and rounded or sub-angular, uniformly sized silica sand
Rubber-Only (R)	Ambiently ground SBR crumb rubber (specify if preference is cryogenically processed) All other proven synthetic and organic infill materials are available
Field Markings:	Tufted, inlaid and painted
Resilient ShockPad:	OPTIONAL: 10 mm (typical) porous composite (100% SBR particles bound with polyurethane) rubber pad (6010SH)