SYSTEM

A-TURF® TITAN



A-Turf® Titan field at Buffalo Bills' Ralph Wilson Stadium – Orchard Park, NY.

OVERVIEW

- Blended parallel-long slit film & monofilament polyethylene fibers in the same stitch.
- Typical rubber & sand or rubber-only infilled.
- 12-year warranty (when installed over an approved pad).

SYSTEM | A-TURF® TITAN







INDUSTRY-BEST SAFETY RATING

A-Turf® Titan system with a ShockPad has the industry's lowest G-Max rating throughout the 12-year warranty period and system's life, making it the safest synthetic turf playing system on the market. It parallels perfectly-conditioned natural grass, for its whole life – up to 15 years!









DATA

Face Yarn Type Polyethylene TenCate XP Blade and Monoslide

Ultra XQ blended in dual yarn types and dual yarn

thicknesses

Yarn Size 12,200 (4 ends/1,800 denier per end for Mono,

5,000 denier per end for XP)

Yarn Thickness 100 microns for XP Blade, 310 microns for

Monoslide Ultra XQ

Pile Weight 50 oz/sy with 2.25" pile height typical, others

available

Finished Pile Height 2.25" typical, others available

Field Color Field Green, Field Green/Lime Green, Field Green/

Olive Green (dual colors as alternating panels or

blended fibers)

Construction Broadloom tufted, 9/3" stitch rate, 1/2" tufting

gauge

Primary Backing TenCate XK TuffBack

Secondary Backing 22 oz/sy urethane typical (required for 12-year

warranty)

Total Product Weight 80 oz/sy (+/- 2 oz) with 2.25" pile height (typical)

Turf Roll Dimensions 15' wide by custom lengths up to 220'

Perforations 3/16" holes on staggered 4" (approximate) centers

Turf Permeability > 20" +/- per hour

Infill Composition Rubber & sand, rubber only, other infills available

Field Markings Tufted, inlaid, painted

Resilient ShockPad OPTIONAL: 10 mm porous rubber pad typical

(ShockPad or approved e-layer required for

12-year warranty)

Specifications are subject to change without notice.



A-Turf Headquarters PO Box 157 Williamsville NY 14231 888-777-6910 **aturf.com**