

OPTIMAL PERFORMANCE FOR ATHLETES. **SUPERIOR VALUE** FOR OWNERS.

SYSTEM A-TURF® TITAN S-50

<image>

A-Turf[®] Titan S-50 field at The SUSA Academy Soccer Club – Islip, NY.

OVERVIEW

- Blended parallel-long slit film & monofilament polyethylene fibers.
- Typical rubber & sand or rubber-only infilled.
- 12-year warranty (when installed over an approved pad).

SYSTEM A-TURF® TITAN S-50



INDUSTRY-BEST SAFETY RATING

A-Turf[®] Titan S-50 system with a ShockPad has the industry's lowest G-Max rating throughout the 12-year warranty period and system's life, making it the safest synthetic turf playing system on the market. It parallels perfectly-conditioned natural grass, for its whole life – up to 15 years!













DATA

Face Yarn Type

Yarn Size

Yarn Thickness

Pile Weight Finished Pile Height Field Color

Construction

Primary Backing Secondary Backing Total Product Weight Turf Roll Dimensions Perforations Turf Permeability Infill Composition

Field Markings Resilient ShockPad

Blended parallel long slit film and monofilament polyethylene fibers in dual yarn types and dual yarn thicknesses Minimum 12,200 (long slit film and monofilament polyethylene fibers combined) Minimum 100 microns for parallel long slit film, 310 microns for monofilament fiber 50 oz/sy 2.0" Field Green and/or Field Green/Lime (dual colors as alternating panels or blended fibers) Broadloom tufted, 10/3" stitch rate, 1/2" tufting gauge ArmourLoc 3L™ 22 oz/sy urethane 80 oz/sy (+/- 2 oz) 15' wide by custom lengths up to 220' 3/16" holes on staggered 4" (approximate) centers > 20" +/- per hour SBR rubber and sand infill (typical), multiple other infill options available Tufted and/or inlaid OPTIONAL: 10 mm porous rubber pad typical (Approved shock pad for approved e-layer required for 12-year warranty)

Specifications are subject to change without notice.



A-Turf Headquarters PO Box 157 Williamsville NY 14231 888-777-6910 aturf.com